

## MANURHIN KMX 732 EVO

**Kind : Swiss-type cnc lathe**  
**Manufacturer : MANURHIN**  
**Model : KMX 732 EVO**  
**Year : 2021**  
**Serial : 287S017**  
**Stock : T14814**



### TECHNICAL DETAILS

- Number of axes	: 7
- Number of spindles	: 2
MAIN SPINDLE	
- Max. bar diameter	: 32 [mm]
- Travel	: 380 [mm]
- Spindle speeds	: 8.000 [rpm]
- Spindle power	: 7,5 / 10,5 [kW]
- C axis indexing precision	: 0,001 [°]
COUNTER-SPINDLE	
- Max. bar diameter	: 32 [mm]
- Z stroke	: 295 [mm]
- Spindle speeds	: 8.000 [rpm]
- Spindle power	: 3,7 / 5,5 [kW]
- C axis indexing precision	: 0,001 [°]
- Number of guide bush holders	: 2
GUIDE BUSH HOLDER 1	
- Number of positions	: 5
- Number of motorized positions	: 3
- X/Y stroke	: 45 / 180 [mm]
GUIDE BUSH HOLDER 2	
- Number of positions	: 5
- Number of motorized positions	: 3
- X/Y stroke	: 45 / 180 [mm]
END ATTACHMENT	
- Number of positions	: 4

**Kind : Swiss-type cnc lathe**  
**Manufacturer : MANURHIN**  
**Model : KMX 732 EVO**  
**Year : 2021**  
**Serial : 287S017**  
**Stock : T14814**

- Number of motorized positions : 3  
- Y stroke : 260 [mm]  
SECONDARY OPERATION  
- Number of positions : 4  
- Number of motorized positions : 3  
\* Y stroke : 260 [mm]  
POWER SUPPLY  
- Supply voltage : 400 [V]  
- Total installed power : 32 [kVA]  
WEIGHT & DIMENSIONS  
- Machine floor space : 3.000 x 1.400 [mm]  
- Machine height : 1.857 [mm]  
- Machine weight : 4300 [kg]  
MACHINE HOURS  
- Number of hours under power : 25310 [h]  
- Number of working hours : 6402 [h]

#### **EQUIPMENT**

- CNC : Fanuc 31i-B  
- Interface : Ethernet / RS232 / USB / PCMCIA  
- 3 colors status lamp  
- Rotating guide bush  
- Parts catcher  
- Ejection of workpiece  
- Coolant tank  
\* with high-pressure pump : HP Muller Combiloop CL2 (2016)  
- Bar loader : LNS Express 332 S2 (2016)  
- Fire extinguisher \*  
NB : working order not guaranteed. To have it checked by a qualified organization of the buyer.  
- Number of turning tool holders : 5  
- Number of fixed tool holders : 10